



Item No. 240902  
**VESA Monitor Mount  
with Tilt Swivel**

For use with all Monitors that has  
the VESA hole pattern on the back

**Installation Instruction**

**Overview Picture**

**Please read all of the instructions and look at the pictures before attaching the ProClip.**

**ProClip USA** may not be held liable for any damage to a vehicle before, during or after the installation or removal of this Holder.

**ProClip USA** may not be held liable for any personal injury resulting from accident or improper use or installation.

**The ProClip** Holder in the installation pictures may look slightly different from the one you have received. However, the same instructions apply.



1. Unscrew the screw in the center of the Vesa Mount and remove the Face Plate from the Tilt Swivel base plate.

Place the Tilt Swivel base plate onto the lower part of the ProClip Dashboard Mount so the center-lined holes in the base plate match the center-lined holes in the ProClip Dashboard Mount. Screw one of the enclosed self-tapping screws through the hole in the Tilt Swivel base plate and into the hole on the lower part of the ProClip Dashboard Mount.



2. Screw one of the enclosed self-tapping screws through the hole in the Tilt Swivel base plate and into the hole on the upper part of the ProClip Dashboard Mount.



3. Place the Mount onto the Tilt Swivel base plate and attach it with the previously removed screw. This screw also controls the pivot, tighter for a firm hold and lose for more (easier) movement/angling of the Mount.

The Mount is now in place as shown in the overview picture above.

